

# PointGard II



ST-1382-2006

The PointGard® II is a microprocessor based stand-alone gas detector for the continuous monitoring of toxic gases and Oxygen in ambient air. The PointGard II is designed to be a stand-alone instrument that is easy to use. The instrument is housed in a rugged NEMA 4X plastic enclosure, has an easy-to-read LED display, plus audible and visual alarm indicators. The instrument is furnished with a 3-prong line cord, which can be plugged into a standard wall outlet.



ST-1382-2006

**PointGard II:**  
Single Point Area Monitor  
for toxic gases in ambient air.

### Simple, quick installation

The instrument is easily mounted on a wall or structure. After installing the sensor, and plugging the line cord into a 110 VAC outlet, PointGard II is ready for operation. Sensors are pre-calibrated before shipment, so calibration is not necessary at start-up. The simple menu guided user interface is accessed through 3 buttons on the front panel of the instrument.

### Proven DraegerSensor technology

The heart of the PointGard II is the electrochemical DraegerSensor®, the latest development in gas sensing technology. The DraegerSensor is designed for accuracy, stability, and long life. Temperature compensation of the sensor signal has been optimized and cross sensitivity to other gases minimized, ensuring an accurate reading of the target gas concentration.

### Complete system

The gas concentration is displayed on a bright LED display. In an alarm condition the horn and the strobes are activated. The measuring ranges can be selected within a number of set points.

PointGard II has an industry standard 4 to 20 mA output, so the current gas concentration can be transmitted to a central control system. The three on-board relays allow for the connection of additional alarm devices in a remote area. The alarm set points can be programmed to any value, and the relays can be programmed as latching/non-, acknowledgeable/non- and rising/falling.

Gas	Range
Ammonia NH <sub>3</sub> LC	0 to 50/100 ppm
Ammonia NH <sub>3</sub> HC	0 to 300/500 ppm
Carbon Monoxide CO	0 to 50/100/ 200/300/500 ppm
Chlorine Cl <sub>2</sub>	0 to 5/10/20/50 ppm
Ethylene Oxide EO	0 to 20/50/100 ppm
Hydrogen H <sub>2</sub>	0 to 500 ppm
Hydrogen Sulfide	0 to 10/20/ H <sub>2</sub> S LC 50/100 ppm
Hydrogen Sulfide	0 to 500 ppm
H <sub>2</sub> S HC	
Hydrogen Peroxide	0 to 5/10/20/50 ppm
H <sub>2</sub> O <sub>2</sub>	
Nitrogen Dioxide NO <sub>2</sub>	0 to 5/10/20/50 ppm
Oxygen O <sub>2</sub>	0 to 5/10/25 Vol%
Sulfur Dioxide SO <sub>2</sub>	0 to 5/10/20/50 ppm

## TECHNICAL DATA

Type	General purpose gas monitor (not to be used in hazardous, classified areas)	
Gases and Ranges	Toxic gases and Oxygen, range user configurable	
Display	3 digit LED display, resolution varies with the range	
Output Signal	Measurement	4 to 20 mA
	Maintenance	4 ± 1 mA 1 Hz modulation, or steady 3 mA; user selectable
	Fault	< 2 mA
Alarms	Two gas concentration alarms (A1 and A2, rising or falling), user-configurable	
Relays	Two alarm relays, one fault relay; normally energized, SPDT, user-configurable for latching/non-, acknowledge/non- and rising/falling.	
	Rating	5A 230 VAC, 5 A 30 VDC
Horn	Volume adjustable from 75 to 100 dB @ 1 ft.	
Supply Voltage	110 VAC or 24 VDC; power cord included	
Ambient conditions	Temperature	+14 to + 122 °F / -10 to + 50 °C
	Pressure	20.7 to 38.4 inch of Hg / 700 to 1300 mbar
	Humidity	5 to 95 %RH (see sensor data sheet)
Enclosure	NEMA 4X, IP 65; lockable by pad lock	
Size (h x w x d approx.)	13.5" x 9" x 5.25", 345 x 230 x 135 mm	
Weight (approx.)	6.9 lbs., 3.1 kg	

## ORDER INFORMATION

PointGard II	45 43 310
PointGard II with 20 ft sensor extender cable	45 43 475
PointGard II with 50 ft sensor extender cable	45 43 477
PointGard II with 100 ft sensor extender cable	45 43 479

### Order sensor separately:

DraegerSensor Ammonia NH <sub>3</sub> LC	68 09 680
DraegerSensor Ammonia NH <sub>3</sub> HC	68 09 645
DraegerSensor Carbon Monoxide CO	68 09 605
DraegerSensor Chlorine Cl <sub>2</sub>	68 09 665
DraegerSensor Ethylene Oxide EO	68 10 740
DraegerSensor Hydrogen H <sub>2</sub>	68 09 685
DraegerSensor Hydrogen Sulfide H <sub>2</sub> S LC	68 09 610
DraegerSensor Hydrogen Sulfide H <sub>2</sub> S HC	68 09 710
DraegerSensor Hydrogen Peroxide H <sub>2</sub> O <sub>2</sub> LC	68 09 705
DraegerSensor Nitrogen Dioxide NO <sub>2</sub>	68 09 655
DraegerSensor Oxygen O <sub>2</sub> LS	68 09 630
DraegerSensor Sulfur Dioxide SO <sub>2</sub>	68 09 660

## SYSTEM CENTERS

### CANADA

Draeger Canada Ltd.  
Mississauga, Ontario L5N 6P9  
Tel +1 905 821 8988  
Fax +1 905 821 2565

### P. R. CHINA

Beijing Fortune Draeger  
Safety Equipment Co., Ltd.  
Beijing 101300  
Tel +86 10 80 49 80 00  
Fax +86 10 80 49 80 05

### FRANCE

Dräger Safety France S.A.S.  
67025 Strasbourg Cedex  
Tel +33 388 40 76 76  
Fax +33 388 40 76 67

### GERMANY

Dräger Safety AG & Co. KGaA  
23560 Luebeck  
Tel +49 451 882 0  
Fax +49 451 882 2080

### MEXICO

Draeger Safety S.A. de C.V.  
Querétaro, Qro. C.P. 76148  
Tel +52 442 246 1113  
Fax +52 442 246 1114

### SINGAPORE

Draeger Safety Asia Pte. Ltd.  
139950 Singapore  
Tel +65 68 72 92 88  
Fax +65 67 73 20 33

### UNITED KINGDOM

Draeger Safety UK Ltd.  
Blyth, Northumberland NE24 4RG  
Tel +44 1670 352 891  
Fax +44 1670 540 033

### USA

Draeger Safety, Inc.  
505 Julie Rivers, Suite 150  
Sugar Land, TX 77478  
Tel +1 281 498 1082  
Fax +1 281 498 5190  
[www.draeger.com](http://www.draeger.com)